

# Pouch Inspector vs Pouch Inspector Light

	Pouch Inspector Light	Pouch Inspector
<b>Compatibility</b>		
Compatible with all known packaging machines	✓	✓
Compatible with all pouches	✓	✓
Compatible with all pills and tablets	✓	✓
<b>Machine features</b>		
Inspection speed	up to 5400 pouches per hour 90 per minute 1,5 per second	up to 18.000 pouches per hour 300 per minute 5 per second
End result	Inspected pouches, unrolled	Inspected pouches, unrolled or on a spool
Inspection grade	high	high
Can process huge quantities	✓	✓
Can process small quantities	✓	✓
Hands free motorized inspection – accepts full spools of pouches for inspection	✓	no
Manually transported inspection – per pouch strip (starts at 1 pouch)	✓	✓
Inspection from right hand side to left hand side	✓	✓
Can inspect repaired pouches	✓	✓
Whole batch can be inspected without interruption	✓	✓
Touchscreen operated	✓	✓
Tolerances per medication adjustable	✓	✓
Changed your mind? Change the configuration on a later point of time	no	Optional (with Cut&Roll)
Automatic separation of alarmed and alarm-free pouch rolls	no	Optional (with Cut&Roll)
Provides pouch roll with a sticker	no	✓
Can be combined with the other configurations for an optimally efficient workflow*	✓	✓
Inspection local on machine	✓	✓
Printable lists and reports (Excel / PDF)	✓	✓
Standard lists and reports	✓	✓
Custom reports	Optional	✓
Modulair purchase model	✓	no
RFID* implementation possibility	no	✓
End-to-end chain control in combination with Track&Trace*	no	✓
<b>Materials</b>		
	Corian, Aluminum, Stainless Steel	Corian, Stainless Steel
<b>Size and weight</b>		
Width	55,5 cm 21.85 inch	40 cm 15.75 inch
Depth	34 cm 13.39 inch	32 cm 12.6 inch
Height	62 cm 24.41 inch	67 cm 26.38 inch
Weight	15 kg 33 pounds	35 kg 77 pounds
Required workplace size (without spool)	Width: 55,5 cm 21.85 inch Depth: 34 cm 13.39 inch	Width: 40 cm 15.75 inch Depth: 32 cm 12.6 inch
Required workplace size (with spool)	Width: 93,4 cm 36.77 inch Depth: 34 cm 13.39 inch	Width: 141 cm 55.51 inch Depth: 32 cm 12.6 inch
<b>Electrical and Operating Requirements</b>		
Power [W]	170	170
Power supply	230 V~, 50-60 Hz	230 V~, 50-60 Hz
Voltage [V]	220 – 240	220 – 240
Amperage [A]	0,8 – 2	0,8 – 2
Net frequency [Hz]	50 – 60	50 – 60
Operation temperature	0 – 40 °C 32 – 104 F	0 – 40 °C 32 – 104 F
Operation humidity	30 – 70 %	30 – 70 %
<b>Operating System</b>		
	Pi Web	Pi Web
Equipped with IMM (Inprocess Model Manager technology)	✓	✓
Web based - Control from any desired device on your network	Optional (with Module WEB BASED)	✓
<b>Support</b>		
Remote	Module SUPPORT	Module SUPPORT
On location	Optional (with Module SUPPORT)	Included in support contract
<b>Quality marks</b>		
GAMP & GMP documented	✓	✓
CE approved	✓	✓
<b>Additions and accessories</b>		
Reel-to-Reel	no	✓
Pi Transport	no (own Pi Light Transport)	✓
Cut&Roll	no	✓
Pouch Winder	✓	✓
Mini Pi	✓	✓
Mini Keyboard	✓	✓
Pi Shaker	no	✓
Spool Spinner round 42 cm	✓	✓
Spool Spinner hexagon 50 cm	no	✓
Spool Spinner hexagon 42 cm	✓	✓

\*Ask for detailed information about our systems and workflows to optimize the production process.